



Roller Lifter Installation Instructions

Thank you for choosing COMP Cams® products! We know you have options in valve train component selection and we are proud to be your manufacturer of choice. Please read this instruction sheet carefully before beginning installation and also take a moment to review the included Limited Warranty information.

Pre-Installation:

It is important for all new roller lifters to be washed thoroughly with mineral spirits or parts washing solvent to remove all assembly grease. After the lifters are cleaned, it is recommended to soak them in common engine oil to ensure bearing saturation.

Installation:

If your new lifters utilize a link bar, inspect them for the word "UP", or an arrow (↑) indicating the direction of installation. These should face toward the center of the engine. It is also recommended to verify lifter bore to lifter clearance. Contact your engine builder or block manufacturer for your specific clearances. After the lifters are installed, it is **NOT** recommended to let the engine sit for a long period of time prior to start up, to help prevent the oil film from breaking down.

Care and Inspection:

Remember, when using solid roller lifters, the only oiling the lifters receive is from windage created by the rotating assembly. Excessive idling or very low rpm usage may cause lack of oil supply to the lifters and cause premature wear to the axles, bearings or roller wheels. This can result in extensive engine damage.

Roller lifters should be inspected periodically for wear to the wheels and or bearings. If valve lash has to be corrected more often than normal, this could be an indication of accelerated lifter wear. Periodic checks are beneficial in determining if your roller lifters need to be rebuilt.

COMP Cams® offers a rebuild program for our solid roller lifters. This procedure includes magnafluxing and polishing the lifter bodies, replacing the axles, bearings, wheels and lock rings for a very nominal charge.

Limited Warranty

Competition Cams, Inc. warrants that all of its products are free from defects in material and workmanship, and against excessive wear for a period of (1) one year from the date of purchase. This **limited warranty** shall cover the original purchaser.

Competition Cams, Inc.'s obligation under this warranty is limited to the repair or replacement of its product. To make a warranty claim, the part must be returned within (1) one year of purchase to the address listed below, freight prepaid. Items covered under warranty will be returned to you freight collect.

It is the responsibility of the installer to ensure that all of the components are correct before installation. We assume no liability for any errors made in tolerances, component selection, or installation.

There is absolutely no warranty on the following:

- A) Any parts used in racing applications;**
- B) Any product that has been physically altered, improperly installed or maintained;**
- C) Any product used in improper applications, abused, or not used in conjunction with the proper parts.**

There are no implied warranties of merchantability or fitness for a particular purpose. There are no warranties, which extend beyond the description of the face hereof. Competition Cams, Inc. will not be responsible for incidental and consequential damages, property damage or personal injury damages to the extent permitted by law. Where required by law, implied warranties or merchantability and fitness are limited for a term of (1) one year from the date of original purchase.

This warranty gives you specific legal rights and you may also have other legal rights, which vary from state to state.



COMP Cams®
3406 Democrat Rd.
Memphis, TN 38118
Phone: (901) 795-2400 Fax: (901) 366-1807
www.compcams.com

Part #122
Revised 6/10/11